



UV-resistant Acrylic Globe

Marine Grade stainless steel latches

Safety bond slots where required

DEC User Interface

Washable Exhaust Filters both sides (exhaust protection by internal positive pressure 24/7)

Hydrophobic HEPA Inlet Filter

Power and Data Conduit Entries, 3/4" US, PG21 Int.

Fix to structure using 4 M12 (1/2") stainless steel bolts (not supplied)

[384]
R15.10

[768]
30.24

[813]
Ø 32.00

[724]
28.50

[412]
16.23

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: MACH ± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±
INTERPRET GEOMETRIC TOLERANCING PER:
MATERIAL
Aluminum & Stainless Steel
FINISH
Powder Coat RAL 9003 White Gloss
DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TB	5/26/2016
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		



TITLE:
Tornado Marine 2000 Lighting Enclosure

SIZE B	DWG. NO. 2000.xxM	REV 01
------------------	----------------------	-----------

SCALE: 1:20 SHEET 1 OF 1