

Fly Configurator

Please complete this form and email to us at info@tempest.biz

Name *		
Company *		
Email *		
Phone		
Projector & Lens Make/Model #	Projector: *	Lens: *
Fly Model *	54.F	Quantity
Destination Country *		
Required by (date) *		
Supply Voltage *		
Options		
FLY RIGGING FRAME	Qty	Type
Thermal Insulation	Qty	
Truss Kit	Qty	
Positive Pressure	Qty	
Set of Feet (landscape)	Qty	
Set of Feet (portrait)	Qty	
Lens Extender Kit	Qty	
Spare Exhaust Cowl	Qty	
Ethernet Comms	Qty	Type
Spare Inlet Filter	Qty	

Custom Requests:

Signal Feedthrough Connectors		
Connector Types (up to six Neutrik D-style feedthroughs) Type:	Position: (indicate type)	Text Label (8 characters Max)
A: Ethercon	1	1
B: OpticalCon	2	2
C: HDMI	3	3
D: Displayport	4	4
E: BNC	5	5
F: Blank	6	6
G: Other:		

Power Inlet Connectors		
North America/Japan: Enclosure/Projector (200-208V) Aux Feed (100-120V)	Fly 25/35 Neutrik PowerCON TRUE1 TOP (20A) IEC C14	Fly 50/50+ Neutrik PowerCON 32A (32A) IEC C14
International: Enclosure/Projector/Aux (230V)	Fly 25/35 Neutrik PowerCON TRUE1 TOP (16A)	Fly 50/50+ Neutrik PowerCon 32A (32A)
Custom Power Connector Requests:		

Factory Use Only:	SO #:	Date:
Electrical:	IEC NEMA	Wiring p:
Test:	Function	Projector
Hardware Kit:		

